

Poly Studio G62 Video Conferencing System With Mounting Plate Kit



*Product image may differ from actual product

Configurable, powerful, all yours

Poly Studio G62 conferencing system features easy setup, seamless integration, and the customization you need. Powerful collaboration tools? Done. Advanced audiovisual options? Check. A flexible setup? You got it¹.

Designed to connect. Made to expand

Transform spaces effortlessly with the Poly Studio G62 video conferencing system, a modular solution designed for increased versatility.

Customize your rooms with confidence

Enjoy richer experiences by adding select Poly peripherals to the Poly Studio G62 video conferencing system without worrying about processing power.

Easy to install. Easier to connect

Pair the Poly Studio G62 video conferencing system with other systems via APIs, and power it up with just a PoE+ for added convenience.

Featuring

Compact. Customizable. Clutter-free

Enjoy easy room integration to select Poly peripherals with the Poly Studio G62 video conferencing system by simply connecting them via Ethernet.

The ultimate setup for collaboration

Block out distractions with Poly DirectorAI and NoiseblockAI by pairing the Poly Studio G62 video conferencing system with Poly peripherals.

Integration-ready, right out of the box

Mount the Poly Studio G62 video conferencing system using the magnetic design and connect it to 3rd party systems for an enhanced experience.

No space? No problem

A simple setup, IP connectivity and one PoE+ powered codec makes the Poly Studio G62 video conferencing system highly adaptable to different spaces.

Device control at your fingertips

Connect and keep an eye on your Poly Studio G62 modular room video conferencing system and Poly peripherals remotely using Poly Lens.

A centralized view of the room

Monitor, manage, and troubleshoot your Poly Studio G62 video conferencing system and peripherals with the Poly Lens cloud-based management service.

Poly Studio G62 Video Conferencing System With Mounting Plate Kit



*Product image may differ from actual product

Specifications

Compatible with

Compatible operating systems: Android

Camera

Smart camera technology: People framing; Group framing; Presenter tracking; DirectorAI perimeter; Speaker framing

Video

People video resolution: 4K, 30 fps (TX and RX) from 2048 Kbps; 1080p, 60 fps from 1740 Kbps; 1080p, 30 fps from 1024 Kbps; 720p, 60 fps from 832 Kbps; 720p, 30 fps from 512 Kbps; 4K, 30 fps from 3200 Kbps

Content video resolution (input): UHD (3840 x 2160); HD (1920 x 1080); WSXGA+ (1680 x 1050); SXGA (1280 x 1024); HD (1280 x 720); XGA (1024 x 768); SXGA+ (1400 x 1050)

Content video resolution (output): UHD (3840 x 2160); HD (1920 x 1080); HD (1280 x 720)

Video frame rate: 30 fps (up to 4K resolution)

Video standards: H.264 AVC; H.264 High Profile; H.265; H.264 SVC; H.263; RTV; H.263 video error concealment; H.264 video error concealment; H.239 Polycom People+Content

Content sharing: Apple AirPlay; Miracast; Digital Whiteboarding; HDMI input; USB Type-C®

Digital signage: Appspace; Raydiant; Zoom

Connectivity and communications

External I/O ports:

2 USB Type-A 5Gbps signaling rate

1 HDMI-in 2.0

1 line in

1 line out

2 HDMI-out 2.0 (video)

1 PoE+ 802.3at-class 4 LAN RJ-45

1 LLN RJ-45

1 USB Type-C® 5Gbps signaling rate (with DisplayPort™ Alt Mode for video input, 2 lanes 4K @ 30 Hz)

Interoperability:

Support for native 3rd party applications including Zoom, Microsoft Teams, Dialpad, GoToRoom, RingCentral and Tencent

Wireless Technology:

802.11 a/b/g/n/ac/ax Wireless; Bluetooth® 5.1; Multiple-Input Multiple-Output (MIMO)³

Audio

Audio features:

Automatic gain control

Automatic noise suppression

Keyboard noise reduction

MMode

NoiseBlockAI

Sound Reflection Reduction

Instant adaptation echo cancellation

Acoustic Fence

Audio error concealment

Siren Lost Packet Recovery technology

Poly Stereo Audio

Active Lip Synchronization

Microphone type: Up to three IP microphone arrays

Audio standards: 22 kHz with Polycom Siren 22 technology; 20 kHz with G.719 (M- Mode) and Polycom Siren 22 technology; 14 kHz with Polycom Siren 14 technology, G.722.1 Annex C; 7 kHz with G.722, G.722.1; 3.4 kHz with G.711, G.728, G.729A

Power supply

Power supply type: External

Operating voltage: 50 - 57 V, 30 W (class 4), 45 W (class 5), 60 W (class 6)

Power features: Power over Ethernet (PoE+), compatible with IEEE 802.3at/bt class 4, 5, 6 switch, or PoE injector^{1,2}

Certifications

Certified collaboration software: Microsoft Teams; Zoom; Poly Video

Environmental

Certifications and compliances: CB; FCC; IC; RCM; VCCI; UL/CSA; CE; WEEE; UKCA; MIC

Operating altitude: 10,000 ft

Operating humidity range: 15 to 80%

Non-operating humidity range: 5 to 95%

Operating temperature range: 32 to 104 °F

Non-operating temperature: -40 to 70 °C -40 to 158 °F

Sustainable impact specifications: 80% post-consumer recycled plastic; Packaging is recyclable; At least 20% recycled metal^{5,6}

Poly Studio G62 Video Conferencing System With Mounting Plate Kit

Specifications

Management

Management software:
Poly Lens

Security

Security management:
802.1x support

Network

Network capabilities: IPv4; IPv6; Auto-MDIX; H.323 and/or SIP up to 6 Mbps in Poly App video mode; Polycom Lost Packet Recovery (LPR) technology; Reconfigurable MTU size; Web proxy support: basic, digest, and NTLM; 100/1G/2.5G; IP REST & CLI API support; Simple Certificate Enrollment Protocol (SCEP)

Weight and dimensions

Product Primary Color: Black
Weight: 1.76 lb
Product dimensions: 9.75 x 6 x 1.38 in
Package weight: 3.07 lb
Package dimensions: 16 x 10 x 5.25 in
Master carton dimension: 16.4 x 5.6 x 10.8 in
Master carton weight: 6.2 lb
Cartons per layer: 18
Pallet (layers): 7
Cartons per pallet: 126
Products per layer: 18
Products per pallet: 126
Pallet weight: 778 lb
Pallet dimensions: 48 x 40 x 80 in
UPC number: 198122558865
Product number: A01KCAA
Product name: Poly Studio G62 Video Conferencing System With Mounting Plate Kit

Warranty

Poly standard one-year limited warranty

Country of origin

Country of origin: Made in Laos

Regulatory

RMN number: PBJ-STG-62R; PBJ-STG-62N

What is in the box

Ethernet cable
Warranty card
HDMI cable
Poly Studio G62

Poly Studio G62 Video Conferencing System With Mounting Plate Kit

Accessories and services (not included)

Poly Studio E70 Smart Camera



The Poly Studio E70 is an intelligent camera that brings clear video quality, and advanced analytics to meeting rooms. Dual cameras are boosted by Poly DirectorAI technology to create a vibrant video experience.

Product number: 842F8AA

Poly G7500 IP Table Microphone

Product number: 874R3AA

Poly Studio G/X/V Bluetooth Remote Control



Product number: 874R8AA

Poly G7500 Studio X IR Remote Control and Receiver



Product number: 875J4AA

Poly TC10 White Touch Controller



The Poly TC10 touch control panel makes meetings more productive and allows users to easily schedule workspaces and conference rooms.

Product number: 875J5AA

Footnotes

Messaging Footnotes

¹ A complete system includes the Poly Studio G62 paired with Poly camera and audio peripherals. Compatible products include Poly Studio E60 camera, Poly Studio E360 companion camera, Poly Studio E70 camera, Poly Studio R30 USB video bar and Poly IP table and ceiling microphones. Compatible devices need to be network connected for management.

Technical Specifications Footnotes

¹ Sold separately. ² PoE+ switch must be configured to 30 W or more. ³ Not available on no radio versions. ⁴ Poly peripherals may be needed to enable these features. ⁵ Recycled plastic is expressed as a percentage of the total weight plastic. Post-consumer recycled is based on the definition set in the EPEAT standard for computers, IEEE 1680.1-2018 standard. ⁶ Recycled metal is expressed as a percentage of the total weight of the metal according to ISO 14021 definitions for metal parts over 25 grams.

© Copyright 2025 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

March 2025
us-en

