

Passive PoE Adapter

Datasheet

POE5460X

54V 60W 10G Passive PoE Adapter



Highlights

- 54V passive PoE supported
- Convenient wall-mount design
- Auto-determine the necessary power requirements
- 1x 10 Gbps/5 Gbps/2.5 Gbps/1 Gbps/100 Mbps/10 Mbps RJ45
- Maximum power up to 60W
- Plug-and-Play, requires no configuration

Overview

The passive PoE adapter POE5460X can be used to simultaneously supply power and transmit data to a passive PoE device, etc.

Product Pictures



Specifications

Hardware Features & Performance

Model		POE5460X
General	Standards	IEEE802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3an, IEEE 802.3bz
	LED	PWR
	Ports	1x 10 Gbps/5 Gbps/2.5 Gbps/1 Gbps/100 Mbps/10 Mbps RJ45 DATA IN port 1x 10 Gbps/5 Gbps/2.5 Gbps/1 Gbps/100 Mbps/10 Mbps RJ45 PWR+DATA OUT port (maximum 60W) 1x AC socket
	Cable Type	10Base-T/100Base-TX: UTP of Cat. 5 or above (maximum 100m) 1000Base-T/2.5GBase-T: UTP of Cat. 5e or above (maximum 100m) 5GBase-T: UTP of Cat. 5e or above (maximum 100m) 10GBase-T: UTP of Cat. 6 or above (maximum 50m) STP of Cat. 6a or above (maximum 90m)
	Output Power	54V/1.11A
	Dimensions	125×59.4×36.8 mm (4.92x2.34x1.45 in)
	Certifications	CE, FCC, BSMI, KC
Physical & Environment	Operating Temperature	-5 °C to 40 °C (23 °F to 104 °F)
	Storage Temperature	-40 °C to 70 °C (-40 °F to 158 °F)
	Operating Humidity	10% to 90% RH non-condensing
	Storage Humidity	5% to 90% RH non-condensing

Some models featured in this guide may be unavailable in your country or region. Visit the Omada by TP-Link website for local sales information: <https://www.omadanetworks.com>. Specifications are subject to change without notice.
© 2025 TP-Link